



HEAT-SHRINK TERMINATIONS (HVT-Z-J/SJ) FOR JCN CABLES (15 - 35 kV)

KEY FEATURES

- Reliable, field proven performance
- Slim profile and lightweight, can be installed upright or inverted
- Non-tracking material is maintenance free even in highly polluted environments
- Fully qualified Class 1 termination per IEEE-48 for a long, trouble free service life
- Unlimited shelf life

TE Connectivity's (TE) Raychem HVT-Z medium voltage termination system features a co-extruded one-piece termination. Unlike the HVT product line, which includes a non-tracking tube and a separate stress control tube, the HVT-Z termination consists of the same proven non-tracking tube together with a co-extruded, built-in stress control grading layer. This stress control layer is based on ceramic semiconductor technology (ZnO) and provides superior discharge and impulse performance.

When the tubing is shrunk down, the coating softens and sticks to irregular surfaces, providing moisture seals as well as electrical stress control. The termination design provides a superior product with a shorter overall length and fewer rain sheds than the HVT product line.

Customers can count on consistent, high quality products, driven by TE's proven innovation and backed by our extraordinary customer support.


PRODUCT SELECTION INFORMATION: DIMENSIONS IN INCHES (mm)

Indoor Kit	Outdoor Kit	Conductor Size (min. - max.)		Insulation Diameter (min. - max.)	Jacket O.D. (max.)
15 kV		15 kV (100%)	15 kV (133%)		
HVT-Z-151-J	HVT-Z-151-SJ	#2 - #1 AWG	-	0.60 - 0.95 (15 - 24)	1.05 (27)
HVT-Z-152-J	HVT-Z-152-SJ	#2/0 - 250 kcmil	#2 - 4/0 AWG	0.80 - 1.05 (20 - 27)	1.45 (37)
HVT-Z-153-J	HVT-Z-153-SJ	350 - 500 kcmil	250 - 500 kcmil	1.05 - 1.40 (27 - 36)	1.9 (48)
HVT-Z-154-J	HVT-Z-154-SJ	750 - 1000 kcmil	750 - 1000 kcmil	1.25 - 2.00 (32 - 51)	2.5 (63)
Installed Length 11.5" (300 mm)					
25 kV/35 kV		25 kV	35 kV		
HVT-Z-252/352-J	HVT-Z-252/352-SJ	#1 - 3.0 AWG	-	0.80 - 1.05 (20 - 27)	1.45 (37)
HVT-Z-253/353-J	HVT-Z-253/353-SJ	#4/0 - 500 kcmil	#1/0 - 4/0 AWG	1.05 - 1.40 (27 - 36)	1.9 (48)
HVT-Z-254/354-J	HVT-Z-254/354-SJ	750 - 1000 kcmil	250 - 1000 kcmil	1.25 - 2.00 (32 - 51)	2.5 (63)
Installed Length 20" (500 mm)					

* Standard package: 1 kit/box.

ORDERING INFORMATION

1. Select the appropriate catalog number. All selections are based on the typical dimensions of 100% and 133% insulated cables manufactured in accordance with the data contained in AEIC CS5 and AEIC CS6, as well as the dimensions of commonly used connectors. Nominal Insulation thickness (100%): 15 kV: 175 mils, 25 kV: 260 mils, 35 kV: 345 mils. Nominal thickness (133%): 15 kV: 220 mils.
2. For cables manufactured to other specifications, confirm selection with cable dimensions.
3. Kits do not contain connectors. Order compression or solder connectors separately.
4. Indoor (-J) kits are suitable for unjacketed and jacketed URD cable.
5. Outdoor (-SJ) kits include skirts for outdoor use and are suitable for unjacketed and jacketed URD cable.
6. Cable mounting brackets are available to accommodate cable diameters from 0.80 - 2.40 inches (20 - 46 mm).

TEST REPORT

Outdoor: 15 kV: EDR-5323, 25-35 kV: EDR-5338
Indoor: 15 kV: EDR-5322, 25-35 kV: EDR5338

te.com/energy

© 2014 TE Connectivity Ltd. family of companies. All Rights Reserved. E577 10/2014

Raychem, TE Connectivity and TE connectivity (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

FOR MORE INFORMATION: TE Technical Support Centers

USA: +1 800 327 6996
France: +33 380 583 200
UK: +44 0870 870 7500
Germany: +49 896 089 903
Spain: +34 916 630 400
Benelux: +32 16 351 731
Canada: +1 (905) 475-6222
Mexico: +52 (0) 55-1106-0800
Latin/S. America: +54 (0) 11-4733-2200
China: +86 (0) 400-820-6015